

tesaflex® 60760 Floor Marking Tape

tesaflex® 60760 is a tough plasticized PVC tape coated with an aggressive modified rubber-resin adhesive, which allows adhesion on many different surfaces. tesaflex® 60760 is even tearable by hand.

Main Application

tesaflex® 60760 is perfectly suitable for temporary and low duty hazard warning & marking of any kind of mobile or static objects.

Technical Data

▪ Backing material	soft PVC	▪ Adhesion to steel	2 N/cm
▪ Total thickness	150 µm	▪ Elongation at break	220 %
▪ Type of adhesive	natural rubber	▪ Tensile strength	33 N/cm

Properties

- Suitable for rough surfaces ●●●●

Evaluation across relevant tesa® assortment: ●●●● very good ●●● good ●● medium ● low

Additional Information

tesaflex® 60760 is also available with two highly visible colour-modes which accord to safety-regulations.

For latest information on this product please visit <http://l.tesa.com/?ip=60760>

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All technical information and data above mentioned are provided to the best of our knowledge on the basis of our practical experience. They shall be considered as average values and are not appropriate for a specification. Therefore tesa SE can make no warranties, expressed or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. The user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.