

tesa® 4308

Masking tape for high demanding masking applications

tesa® 4308 is a slightly crêped paper masking tape which withstands temperatures up to 100°C. It can be used either with 2 component or water based paints. The backing avoids penetration or suffusing of lacquer or paint.

tesa® 4308 can be removed easily without any residues.

It always leaves clean paint results with sharp paint edges.

Main Application

tesa® 4308 has been developed especially for high demanding masking applications in the CBR and transportation industry.

Technical Data

▪ Backing material	slightly-creped paper	▪ Elongation at break	13 %
▪ Total thickness	170 µm	▪ Tensile strength	53 N/cm
▪ Type of adhesive	natural rubber	▪ Temperature resistance	100 °C
▪ Adhesion to steel	4 N/cm		

Properties

▪ Hand tearability	● ● ● ●	▪ Sharp colour edge	● ● ● ●
▪ Easy to remove	yes	▪ Conformability	● ● ●
▪ Paint anchorage	● ● ● ●		

Evaluation across relevant tesa® assortment: ● ● ● ● very good ● ● ● good ● ● medium ● low

For latest information on this product please visit <http://l.tesa.com/?ip=04308>

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All technical information and data above mentioned are provided to the best of our knowledge on the basis of our practical experience. They shall be considered as average values and are not appropriate for a specification. Therefore tesa SE can make no warranties, expressed or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. The user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.