

productinformation

tesa® 4333 PV1 Precision Mask® Sensitive

Professional masking tape for precise and flat paint edges on sensitive surfaces

The masking tape tesa® Precision Mask® 4333 is perfectly suited for painting work on sensitive surfaces such as wall coverings, wallpaper and varnished surfaces. As a professional masking tape it is extremely gentle yet still sticks firmly. Therefore it prevents paint tears without damaging the surface. This innovative professional masking tape comprises a tear-proof, extremely thin special backing which is coated with an acrylate adhesive compound and is particularly easy to use. This new masking tape was developed especially for applications where maximum precision is vital.

Main Application

- This tape is suited for almost all indoor paint works
- tesa® 4333 PV1 Precision Mask® Sensitive is applicable with water-based paints and lacquers and fits even for high-class spatula techniques
- It is especially designed for applications on sensitive and critical surfaces
- The flat backing material is highly conformable to the surface and leads to precise razor-sharp paint edges

Technical Data

| | | | |
|--------------------|------------|-----------------------|----------|
| ▪ Backing material | flat paper | ▪ Adhesion to steel | 0.5 N/cm |
| ▪ Total thickness | 80 µm | ▪ Elongation at break | 5 % |
| ▪ Type of adhesive | acrylic | ▪ Tensile strength | 32 N/cm |

Properties

| | | | |
|-----------------------------------|--|---------------------|--|
| ▪ Suitable for sensitive surfaces | | ▪ Paint anchorage | |
| ▪ Suitable for rough surfaces | | ▪ Sharp colour edge | |

Evaluation across relevant tesa® assortment: very good good medium low

Additional Information

Please note that adhesive tapes should not be left on sensitive surfaces for longer than one week as after that the protected surfaces might get damaged during the de-masking of the tape. Before using an adhesive tape on a delicate surface, please make a trial application for up to 24 hours.

For latest information on this product please visit <http://l.tesa.com/?ip=04333>

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All technical information and data above mentioned are provided to the best of our knowledge on the basis of our practical experience. They shall be considered as average values and are not appropriate for a specification. Therefore tesa SE can make no warranties, expressed or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. The user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.