

## tesa® Professional 4024 Universal carton sealing tape

tesa® 4024 is a universal carton sealing tape that comprises a substrate of PP film coated with a special adhesive mass of acrylate (HiTack). The solvent-free sealing tape is especially known for its particularly high adhesive strength, which allows packages to be sealed securely immediately after application. Furthermore, the carton sealing tape can be handled easily by all tesa® manual dispensers, allowing it to be unrolled with very little noise. Due to its high level of resistance to UV light, ageing and temperatures, the adhesive tape offers an extended service life.

### Main Application

- Packaging and closing \* Sealing of light and medium-range weight cartons

### Technical Data

▪ Backing material	PP film	▪ Adhesion to steel	3 N/cm
▪ Total thickness	52 µm	▪ Elongation at break	140 %
▪ Type of adhesive	acrylic	▪ Tensile strength	45 N/cm

### Properties

▪ Automatic application	yes	▪ Printability	●●●
▪ Manual application	yes	▪ Low noise unwinding	yes

Evaluation across relevant tesa® assortment: ●●●● very good ●●● good ●● medium ● low

For latest information on this product please visit <http://l.tesa.com/?ip=04024>

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All technical information and data above mentioned are provided to the best of our knowledge on the basis of our practical experience. They shall be considered as average values and are not appropriate for a specification. Therefore tesa SE can make no warranties, expressed or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. The user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.

## tesa® Professional 4024 Universal carton sealing tape

tesa® 4024 is a universal carton sealing tape that comprises a substrate of PP film coated with a special adhesive mass of acrylate (HiTack). The solvent-free sealing tape is especially known for its particularly high adhesive strength, which allows packages to be sealed securely immediately after application. Furthermore, the carton sealing tape can be handled easily by all tesa® manual dispensers, allowing it to be unrolled with very little noise. Due to its high level of resistance to UV light, ageing and temperatures, the adhesive tape offers an extended service life.

### Main Application

- Packaging and closing \* Sealing of light and medium-range weight cartons

### Technical Data

▪ Backing material	PP film	▪ Adhesion to steel	3 N/cm
▪ Total thickness	52 µm	▪ Elongation at break	140 %
▪ Type of adhesive	acrylic	▪ Tensile strength	45 N/cm

### Properties

▪ Automatic application	yes	▪ Printability	●●●
▪ Manual application	yes	▪ Low noise unwinding	yes

Evaluation across relevant tesa® assortment: ●●●● very good ●●● good ●● medium ● low

For latest information on this product please visit <http://l.tesa.com/?ip=04024>

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All technical information and data above mentioned are provided to the best of our knowledge on the basis of our practical experience. They shall be considered as average values and are not appropriate for a specification. Therefore tesa SE can make no warranties, expressed or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. The user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.