

# productinformation

## tesa® 4318 PV2

High performance paper masking tape up to 160 °C

tesa® 4318 PV2 is a finely crêped, flexible paper masking tape, especially suitable for the high requirements of paintworks (water- or solvent based paints) followed by oven-drying.

### Technical Data

▪ Backing material	slightly-creped paper	▪ Elongation at break	12 %
▪ Total thickness	170 µm	▪ Tensile strength	47 N/cm
▪ Type of adhesive	natural rubber	▪ Temperature resistance	160 °C
▪ Adhesion to steel	4 N/cm		

### Properties

▪ Hand tearability	●●●●	▪ Sharp colour edge	●●●
▪ Easy to remove	yes	▪ Conformability	●●●
▪ Paint anchorage	●●●●		

Evaluation across relevant tesa® assortment: ●●●● very good ●●● good ●● medium ● low

### Additional Information

Paints and even critical filler systems adhere very well to the backing avoiding any kind of flaking.

tesa® 4318 PV2 can be removed from rubber, glass and paint without leaving adhesive residues.

For latest information on this product please visit <http://l.tesa.com/?ip=04318>

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All technical information and data above mentioned are provided to the best of our knowledge on the basis of our practical experience. They shall be considered as average values and are not appropriate for a specification. Therefore tesa SE can make no warranties, expressed or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. The user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.