

tesa® 4843

Premium plastering protection tape to protect sensitive profiles and facings

The tesa® plastering protection tape won't let you down at any time of year, because the sturdy tape will stick reliably even when it's cold. This means it provides optimum protection for painting, stucco and plastering work. It comprises a supple, tear-resistant, soft PVC film and is coated with a special aging-resistant adhesive compound. The plastering masking tape protects the surfaces of sensitive profiles, frames and facing from soiling or damage through plastering material or tools. The tape is insensitive to humidity, weak acid and alkaline solutions as well as to many chemicals.

Main Application

- Outdoor applications
- Good protection of smooth and slightly rough surfaces
- For applications that require high adhesion power (e.g. plastering, painting, gypsum, masonry and stucco work)
- Also suitable for the sealing of bags, heavy duty wrapping and other DIY applications
- For temperatures above 0°C

Technical Data

▪ Backing material	PVC film	▪ Elongation at break	200 %
▪ Total thickness	122 µm	▪ Tensile strength	23 N/cm
▪ Type of adhesive	natural rubber	▪ UV-resistance	2 weeks
▪ Adhesion to steel	1.2 N/cm		

Properties

▪ Hand tearability	● ● ●	▪ Sharp colour edge	● ● ● ●
▪ Suitable for rough surfaces	● ● ● ●	▪ Conformability	● ● ● ●
▪ Paint anchorage	● ● ●		

Evaluation across relevant tesa® assortment: ● ● ● ● very good ● ● ● good ● ● medium ● low

For latest information on this product please visit <http://l.tesa.com/?ip=04843>

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All technical information and data above mentioned are provided to the best of our knowledge on the basis of our practical experience. They shall be considered as average values and are not appropriate for a specification. Therefore tesa SE can make no warranties, expressed or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. The user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.