

## tesa® 4848 PV1 Surface protection film

tesa® 4848PV1 surface protection film features an environmentally friendly polyethylene backing and a light, age-resistant acrylic adhesive.

This ensures easy, residue-free removal within four weeks of application.

The protection film is resistant against different chemical ingredients, physical stress and moisture.

The transparent backing avoids a "darkroom" effect when the film is applied to windows.

### Main Application

Protection against dirt and damage during

- paint-
- plaster-/stucco-
- facade- work

### Technical Data

▪ Backing material	PE film	▪ Adhesion to steel	0.8 N/cm
▪ Total thickness	48 µm	▪ Elongation at break	200 %
▪ Type of adhesive	acrylic	▪ Tensile strength	12 N/cm

### Properties

- Easy to remove
- yes

### Additional Information

Outdoor applications make great demands on self-adhesive tapes and require increased accuracy regarding the substrate testing. Especially old and weathered substrates - PVC and coated metals in particular - can lead to residues or ghosting after removal.

For latest information on this product please visit <http://l.tesa.com/?ip=04848>

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All technical information and data above mentioned are provided to the best of our knowledge on the basis of our practical experience. They shall be considered as average values and are not appropriate for a specification. Therefore tesa SE can make no warranties, expressed or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. The user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.